



TAURUS  
CRACO



# INNOVATIONS 21.0


BARTH > Catalogue 2021 > English



LIFTING TABLES




ASSEMBLY TABLES



TURNING/ROTATING



VACUUM PRESSES



BONDING PRESSES



GRINDING MACHINE

[www.tauruscraco.com](http://www.tauruscraco.com)



TAURUS  
CRACO

Overview of

# BARTH lifting and assembly tables

H 300

Page 06



- › Worktop: 1,245 x 740 mm
- › Max. load: 300 kg

H 350 XL

Page 08



- › Worktop: 2,000 x 1,015 mm
- › Max. load: 350 kg

H 600

Page 10



- › Worktop: 2,000 x 1,015 mm
- › Max. load: 600 kg

H 850

Page 10



- › Worktop: 2,000 x 1,015 mm
- › Max. load: 850 kg

H 1000

Page 12



- › Worktop: 2,000 x 1,015 mm
- › Max. load: 1,000 kg

vakuuCAR

Page 16



- › Worktop: 1,350 / 1800 x 800 mm
- › Max. load: 75 kg

vakuuLIFT-S

Page 18



- › Worktop: 2,000 x 1,015 mm
- › Max. load: 350 kg



... more  
DETAILS!

Instant information:

+1 905 451 8430



TAURUS  
CRACO

BARTH

## The power package with quick stroke Lifting table H 600 / H 850

The work and lifting tables of the 600 or 850 series handle more weight without any problems. Workpieces up to a weight of 600 kg or 850 kg can be processed, lifted and transported without any problems. Height adjustment is ensured by a 2-step quick stroke hydraulic system and can be adjusted continuously from 450 mm to 1,100 mm.



The foot pump chooses automatically the right step:  
1st step: Quick lift for small loads  
2nd step: Easy lift for loads of 600 kg or 850 kg



### Base version of lifting table H 600 / 850

- › Lifting table 600, without worktop, Load capacity 600 kg
- › Lifting table 850, without worktop, Load capacity 850 kg
- › 2 steering rollers with brake
- › 2 castors
- › 2-step foot-pumped hydraulic system, optionally attached to the front or longitudinal side
- › Footprint L x W x H:  
2,000 x 1,015 x 450 – 1,100 mm

Various accessories such as hole plates, longitudinal pull-outs are available. Refer to pages 13 and 21





# TAURUS CRACO

## Lifting table H 600 / H 850



### SMOOTH-RUNNING

2-step quick stroke hydraulic system with automatic speed adjustment



### MOBILE

2 steering wheels fitted with a brake, 2 castors



### ERGONOMIC

the suitable working height can always be selected between 450 - 1,100 mm



### STURDY

solid steel structure, powder-coated surfaces



### FLEXIBLE

depending on the application, with optional extensions, with adjustable size



Lifting table H 850 with optional worktop



For worktops, refer to page 13



**Comfort**  
The foot pump chooses automatically the right step:  
1. step: Quick lift for small loads  
2nd step: Easy lift for loads up to 600 kg or 850 kg

02

**Sturdy scissors-type structure**  
for uniform load holding

04

**High-quality castors**  
smooth-running, 2x with brake  
and 2x fixed castors

01

**Solid, torsion-resistant base structure**  
height adjustable: 450–1,000 mm

03

**Optional worktop or hole plate**  
2,000x1,015x30 mm. With longitudinal pull-outs of 550mm on both sides available. Accessories for hole plate, refer to page 21

05

[www.tauruscraco.com](http://www.tauruscraco.com)