



3 HEAD LSJ 600 3R WIRE BRUSH MACHINE



282 Orenda Road, Brampton, ON, L6T 4X6



800.386.5222



www.tauruscraco.com

FEATURES >>

The Wire Brush Machine is primarily utilized for enhancing the surface of various materials such as solid wood panels, flooring, and grooves. It effectively brushes the surface to create a textured, natural wood grain appearance, highlighting the main and secondary patterns. This process enhances the wood's visual appeal and makes subsequent processing more prominent.

Its applications include embossed flooring, textured surface treatments for furniture boards, decorative plate processing, wood veneer treatments, and straight surface processing for wood-plastic composite boards, among others.

Features:

- 1. Working width of belt: 600 mm
- 2. Actual processing thickness: 0.3 80 mm
- 3. The lower supporting roller or belt feeding mode, feed speed can be adjusted
- 4. Feed table structure of multiple choice, the height can be accurately lifting or remain unchanged
- 5. 140 mm or 5.5" port per head

Boss 3 Head LSJ 600 3R Wire Brush Machine	
Max working width	600 mm
Max working thickness	80 mm
1st wire brush roller motor	7.5 kW (inverter)
Wire diameter on 1st wire brush roller	0.5 mm
2nd wire brush motor	7.5 kW (inverter)
Wire diameter on 2nd wire brush roller	0.3 mm
3rd dupont wire brush motor	5.5 kW
Feeding motor	1.5 kW (inverter)
Lifting motor	0.37 kW
Oscillating motor	0.06 kW x 3
Total motor power	21.18 kW
Feeding speed	5-19 m/min
Overall dimensions	2250 x 1550 x 1700 mm
Weight	2000 kg

FINANCIAL TERMS >>

FINANCIAL TERMS:

30% deposit payment with signed order.

60% payment due upon notification of machine shipment Ex-Factory.

10% payment due upon completion of installation, not to exceed 30 days after delivery





282 Orenda Road, Brampton, ON, L6T 4X6



800.386.5222



www.tauruscraco.com

