



**TAURUS
CRACO**

282 Orenda Road West,
Brampton, ON L6T 4X6
800-386-5222
www.tauruscraco.com
sales@tauruscraco.com



C-1203 Coping/End Matching System

Features:

- Chip-free Coping or Tenoning of either square or profiled parts without the need of a backup piece or chip braker.
- Two counter rotating spindles 1 1/4" Diameter, rotation at 7000 rpm's
- Tooling change take approximately two minutes or less.
- The C-1203 can also be used for End-Matching.
- Material hold clamp always parallel to work table.
- THK style rails for guidance of carriage stroke and hold down clamp.
- UL LISTED



Specifications:



5 HP Motor, 3Phase 230/460 volt
(wired 230 volt standard). Specify Voltage.

Maximum Cutter Diameter: 5" OD
Minimum Cutter Diameter: 3 1/2" OD
Maximum capacity of wood: 2" thick by 9 1/2" wide

Unlimited Length of part
Minimum thickness: 11/16"
(can be modified to do 1/2")

Minimum Length of part: 3"
Cycle time: 4 to 10 seconds,
(adjustable)

Dust Outlet Diameter: 5"
Machines weight approx.: 957 lbs





**TAURUS
CRACO**

282 Orenda Road West,
Brampton, ON L6T 4X6
800-386-5222
www.tauruscraco.com
sales@tauruscraco.com



OPTIONS FOR C-1203 & C-1205

Aluminum sub-table for the stacking of tooling

Upgrade to 7.5HP (For model C-1203)

5HP, 230 Volt Single Phase Motor (for C-1203 & C-1205)

5HP, 3 Phase, 50 Hz motor for our European Customers

Change Voltage to 460 Volt

Remove motor & electrical controls

Custom base late to allow larger diameter cutters

(WARNING: this will increase the minimum width of the work piece you can cope)

2nd side pressure clamp to use with sub-table when stacking tooling

Micro-adjustable back fence

Installation and training (plus all expenses)

Service call for out of warrant machines (plus all expenses)

Freight to Brampton, ON including Hydro Inspection